

Bush Hog® TOUGH 278 Series Rotary Cutters

LIMITED AVAILABILITY

BUSH HOG® TOUGH FEATURES

TOUGH 9 Gauge Deck

TOUGH 9 Gauge Sidebands

TOUGH Rigid Strongback

TOUGH Standard Dual Wheel

TOUGH Round Bladeholders

TOUGH Powder Coat Paint



MODEL	278
Cutting Width	8 ft
Cutting Capacity	Up to 2 inch Diameter
Offset	78 ¹ / ₂ inches
Dimensions (width x length)	8 ft 5 inches x 7 ft 3 inches
Transport Width	101 inches
Type Hitch	3 Point Category II, Category II Quick Hitch or Pull
Cutting Height	2 ¹ / ₂ to 10 inches (Lift), 2 ¹ / ₂ to 12 inches (Pull)
Deck Thickness	9 gauge
Sidebands	9 gauge x 7 ³ / ₈ inches
Minimum Tractor HP	40 PTO (Pull), 55 PTO (Lift)
Driveline	ASAE Category 4
Cross Shaft	Rubber element
Gearbox HP	Main - 70, Outboard - 50
Tractor PTO Speed	540 RPM
Driveline Protection	Slip clutch, 4 Plate PTO Slip Clutch Available
Height Adjustment	Manual
Blade Holder(s)	Round
Blades	1/2 x 4 inches, Uplift
Blade Tip Speed	16,856 FPM
Tires	Dual laminated standard
Axles	Dual tailwheels
Deflectors	Front Belting and Rear Bands standard, Chains optional
Safety Tow Chain	Standard on pull model
Approximate Weight	1100 lbs (Lift), 1300 lbs (Pull)
Options	Highway Chains, Hydraulic Adjustment or Ratchet for Pull Models, Jackstand, Dual Tailwheels
Warranty	1 year limited warranty