

Bush Hog® TOUGH

4215 Series Rotary Cutters

BUSH HOG® TOUGH FEATURES

TOUGH 10 Gauge Deck Construction

TOUGH 7 Gauge Steel Strongbacks

TOUGH 1/4 Inch Sidebands

TOUGH Spring Shock Absorbers On Each Axle Arm

TOUGH Heavy Duty Axles

TOUGH Powder Coat Paint



MODEL	4215
Cutting Width	15 ft
Cutting Capacity	2 inch Diameter
Dimensions (width x length)	15 ft 7 inches x 12 ft 2 inches
Transport Width	15 ft 7 inches
Type Hitch	3 Point Cat. II & III Standard & Quick Hitch
Cutting Height	2 to 16 inches
Deck Thickness	10 gauge
Side Bands	1/4 x 10 inches
Minimum Tractor HP	125 PTO
Driveline	ASAE Cat. 5, for 1000 PTO speed tractors only
Cross Shaft	Slipclutch
Gearbox HP	(3) 160 - Center, 110 - Outboard
Tractor PTO Speed	1000 RPM
Driveline Protection	(3) 2 Plate Slip Clutch
Height Adjustment	Choice of Manual Height Bundle or Hydraulic
Blade Holders	Round or Straight
Blades	1/2 x 4 inches - Uplift
Blade Tip Speed	17,280 FPM (Center), 15,708 FPM (Outboard)
Tires	Laminated
Axles	Single Tires Only
Deflectors	Front Belting and Rear Band
Approximate Weight (Pull with Single Axle)	3911 lbs
Highway Lighting	Standard
Options	Single Tailwheel for Lift, Grass Baffle Kit, Shredding Kit 30/38/40 inch Rows
Warranty	1 year limited warranty with a 1 year gearbox limited warranty