

Single-Spindle Rotary Cutters



BUSH HOG®

IF IT DOESN'T SAY
BUSH HOG®
IT JUST WON'T CUT IT™

RAZORBACK SERIES | BH200 SERIES | BH300 SERIES |
BH400 SERIES | BH500 SERIES



RAZORBACK SINGLE-SPINDLES

RAZORBACK SERIES
ROTARY CUTTERS

BH4 / BH5 / BH6



Get tough on weeds and grass with a Razorback!

The Razorback Series has Bush Hog®'s legendary durability and reliability built into each of the three models. Ideal for weeds, grass, and up to 1-inch diameter brush, these models are economically priced for use around estates and small farms. The price and value of the Razorback Series units once again prove that nothing beats a Bush Hog®!

Razorback Series Features

- **"C" Channel Sideband** in 10-gauge x 8-inches
- **Laminated Tires** built to last and durable in the roughest conditions
- **Gearbox Rating** of 60 HP
- **Floating Top Hitch Link** with a 3-point lift
- **Cutting Widths** from 4 to 6-feet and up to 1-inch diameter
- **Bush Hog® Blades** built to tear through varied vegetation



RAZORBACK SERIES SINGLE-SPINDLE SPECIFICATIONS

MODELS:	BH4	BH5	BH6
Cutting Width	4-feet	5-feet	6-feet
Cutting Capacity	Up to 1-inch Diameter		
Cutting Height (Minimum)	2-inches		
Type Hitch	3-Point Lift, ASAE Cat. 1 Standard		
Deck Thickness	14-gauge	12-gauge	
Side Bands	“C” Channel, 10-gauge x 8-inches		
Driveline	ASAE Cat. 3		
Gearbox Rating	60 HP*		
Tractor PTO Speed	540 RPM		
Driveline Protection	Shearbolt or Slipclutch		
Bladeholder	Oval Pan		
Blades	1/2-inch X 3-inches		
Blade Tip Speed	14,632 FPM	15,497 FPM	14,307 FPM
Tires	Laminated		
Tractor PTO HP (Minimum)	15 HP	20 HP	25 HP
Front and Rear Deflectors	Rubber front, Rear metal band		
Approximate Weight	393-lbs.	491-lbs.	577-lbs.
Warranty	1-year limited warranty		
Gearbox Limited Warranty	3-years		
Color	Available in Red, Green, Orange, Blue		

*Field Performance Rating

BH200 SINGLE-SPINDLES

BH200 SERIES
ROTARY CUTTERS

BH215 / BH216 / BH217



Bush Hog®'s Legendary Single-Spindle Rotary Cutters

Grass, weeds, and small brush are no match for these authentic Bush Hog® built cutters. Available in 5-foot, 6-foot, and 7-foot cutting widths, the BH200 Series Rotary Cutters are designed to deliver superior performance in tough conditions, day after day, year after year.

***When you buy Bush Hog®, you're buying
the name synonymous with the task.***

BH200 Series Features

- **Strongbacks and Gearbox Stand** are located under the deck creating a smooth-top for easy cleaning.
- **Taller Sidebands** allow more material and airflow under the deck increasing cutting volume and clipping efficiency.
- **1/4" Skids** run half the length of the cutter to protect the sidebands and add strength and stiffness.
- **Rear Band** is continuously welded and curved to add strength and resist bending.
- **Formed Tailwheel Bracket** is fully welded to the deck providing superior strength during punishing vertical and horizontal loads.
- **Arched Struts** maintain rigidity from front to back, while the flexible link allows the cutter to follow land contours.
- **Smooth-top Deck** makes clean-up a snap.
- **Gearboxes** are put through the paces during custom-designed lab tests that mimic real-world conditions and obstacles like rocks and stumps, while hundreds of hours in field performance tests prove that these cutters are Bush Hog® Tough.
- **Lower Double Hitch Lugs** are welded to the strongbacks providing greater overall hitch and deck strength.
- **Laminated Tailwheels** are puncture-proof and caster effortlessly through all kinds of terrain.



BH200 SERIES SINGLE-SPINDLE SPECIFICATIONS

MODELS:	BH215	BH216	BH217
Cutting Width (in)	60	72	84
Cutting Height (in)	2 - 12		1 - 10
Cutting Capacity (in)	2		
Hitch Type	Cat 1 Std & QH Compatible; Cat 2 Std Only		Cat 1 or 2 Std & QH
Deck Thickness (ga)	11	10	
Sidebands	11-1/2" x 11 ga	11-1/2" x 10 ga	11-3/4" x 10 ga
Driveline	ASAE Cat 3		
Driveline Protection	Shearbolt or Slip-Clutch		Slip-Clutch Standard
Gearbox Rating (PTO)	65		130
Tractor PTO Speed	540		
Minimum Tractor HP	25	30	50
Blade Holder	Oval		
Blades (in)	1/2 x 4 uplift		
Blade Tip Speed (FPM)	14335	14963	
Tires	16" Laminated		
Safety Shielding	Front and Rear Deflectors or Chains		
Approximate Weight (lbs)	655	804	1036
Warranty	6 Year Gearbox Warranty and 1 Year Limited Machine Warranty		
Color	Available in Red, Green, Orange, Blue		

BH300 SINGLE-SPINDLES

**BH300 SERIES
ROTARY CUTTERS**

BH315 / BH316 / BH317



Powerful features to mow down tough vegetation!

Dense grass, tough weeds, and thick brush are no match for these authentic Bush Hog® built cutters. Available in 5-foot, 6-foot, and 7-foot cutting widths, the BH300 Series Rotary Cutters are at the heart of the single-spindle lineup. Effective. Rugged. Dependable. These cutters deliver performance day in and day out.



BH300 Series Features

- **Strongbacks and Gearbox Stand** are located under the deck creating a smooth-top for easy cleaning.
- **Taller Sidebands** allow more material and airflow under the deck increasing cutting volume and clipping efficiency.
- **Replaceable 1/4" Skids** run half the length of the cutter to protect the sidebands and add strength and stiffness.
- **Rear Band** is continuously welded and curved to add strength and resist bending.
- **Formed Tailwheel Bracket** is fully welded to the deck providing superior strength during punishing vertical and horizontal loads.
- **Arched Struts** maintain rigidity from front to back, while the flexible link allows the cutter to follow land contours.
- **Smooth-top Deck** makes clean-up a snap.
- **Lower Double Hitch Lugs** are welded to the strongbacks providing greater overall hitch and deck strength.
- **Gearboxes** are put through the paces during custom-designed lab tests that mimic real-world conditions and obstacles like rocks and stumps, while hundreds of hours in field performance tests prove that these cutters are Bush Hog® Tough.
- **Laminated Tailwheels** are puncture-proof and caster effortlessly through all kinds of terrain.



BH300 SERIES SINGLE-SPINDLE SPECIFICATIONS

MODELS:	BH315	BH316	BH317
Cutting Width (in)	60	72	84
Cutting Height (in)	2 - 12		
Cutting Capacity (in)	3		
Hitch Type	Cat 1 or 2 Std & QH Compatible		Cat 2 or 3 Std & QH
Deck Thickness (ga)	10		
Sidebands	11-1/2" x 1/4"		11-3/4" x 1/4"
Driveline	ASAE Cat 4		
Driveline Protection	Slip-Clutch		
Gearbox Rating (PTO)	130		
Tractor PTO Speed	540		
Minimum Tractor HP	35	45	55
Blade Holder	Round		
Blades (in)	1/2 x 4 uplift		
Blade Tip Speed (FPM)	14,600	15,000	14,450
Tires	16" Laminated		Single or Dual 16" Laminated
Safety Shielding	Front and Rear Deflectors or Chains		
Approximate Weight (lbs)	890	1,050	1,250
Warranty	6 Year Gearbox Warranty and 1 Year Limited Machine Warranty		
Color	Available in Red, Green, Orange, Blue		

BH400 SINGLE-SPINDLES

**BH400 SERIES
ROTARY CUTTERS**

BH416 / BH417



Bush Hog®'s Legendary Heavy-Duty Single-Spindles

Thick pastures, roadsides, gas and power line right-of-ways are no match for these authentic Bush Hog® built cutters. Available in 6- and 7-foot cutting widths, the BH400 Series Rotary Cutters are designed and built to take down virtually any unwanted vegetation. Whether you're a professional cutting every day or a weekend warrior tackling tough jobs on the farm, these cutters will be with you every step of the way.

BH400 Series Features

- **Strongbacks and Gearbox Stand** are located under the deck creating a smooth-top for easy cleaning.
- **Taller Sidebands** allow more material and airflow under the deck increasing cutting volume and clipping efficiency.
- **1/4" Skids** run half the length of the cutter to protect the sidebands and add strength and stiffness.
- **Rear Band** is continuously welded and curved to add strength and resist bending.
- **Gusseted Tailwheel Bracket** is reinforced in critical wear areas to provide increased strength and durability.
- **Arched Struts** maintain rigidity from front to back, while the flexible link allows the cutter to follow land contours.
- **Tubular-Style Hitch Components** resist bending and twisting even in the most extreme conditions.
- **Quick Hitch** compatibility allows for easier cutter attachment saving you time and energy.
- **Reinforced Tailwheel Casters** are designed to withstand extreme punishment, while the increased rolling radius of the 21" laminated tires casters effortlessly over uneven ground.
- **Heavy-Duty Gearboxes** are put through the paces during custom-designed lab tests that mimic real-world conditions and obstacles like rocks and stumps, while hundreds of hours in field performance tests prove that these cutters are Bush Hog[®] Tough.

BH400 SERIES SINGLE-SPINDLE SPECIFICATIONS

MODELS:	BH416	BH417
Cutting Width (in)	72	84
Cutting Height (in)	2 - 12	
Cutting Capacity (in)	4	
Hitch Type	Cat 2 or 3 Std & QH	
Deck Thickness (ga)	7	
Sidebands	13" x 1/4"	
Driveline	ASAE Cat 5	
Driveline Protection	2-Plate Slip-Clutch	4-Plate Slip-Clutch
Gearbox Rating (PTO)	210	
Tractor PTO Speed	540	
Minimum Tractor HP	60	70
Blade Holder	Round	
Blades (in)	1/2 x 4 uplift (5" available)	1/2 x 4 uplift
Blade Tip Speed (FPM)	13,997	14,488
Tires	Single 21" Laminated	Dual 21" Laminated
Safety Shielding	Single or Double Row Chains	
Approximate Weight (lbs)	1300	2000
Warranty	6 Year Gearbox Warranty and 1 Year Limited Machine Warranty	

BH500 SINGLE-SPINDLES

**BH500 SERIES
ROTARY CUTTERS**

BH516



Bush Hog®'s Legendary Heavy-Duty Single-Spindle Rotary Cutters

Thick pastures, gas and power line right of ways, roadsides, even small forests are no match for these authentic Bush Hog® built cutters. Available in a 6-foot cutting width, the BH500 Series Rotary Cutters are designed and built to take down virtually any unwanted vegetation. Whether you're a professional cutting every day or a weekend warrior tackling tough jobs on the farm, these cutters will be with you every step of the way.

BH500 Series Features

- **Reinforced Strongbacks and Gearbox Stand** are integrated together and located under the deck creating a smooth-top for easy cleaning.
- **Taller Sidebands** allow more material and airflow under the deck increasing cutting volume and clipping efficiency.
- **1/4" Skids** run half the length of the cutter to protect the sidebands and add strength and stiffness.
- **Rear Band** is continuously welded and curved to add strength and resist bending.
- **Gusseted Tailwheel Bracket** is reinforced in critical wear areas to provide increased strength and durability.
- **Arched Struts** maintain rigidity from front to back, while the flexible link allows the cutter to follow land contours.
- **Tubular-Style Hitch Components** resist bending and twisting even in the most extreme conditions.
- **Quick Hitch** compatibility allows for easier cutter attachment saving you time and energy.
- **Reinforced Tailwheel Casters** are designed to withstand extreme punishment, while the increased rolling radius of the 21" laminated tires casters effortlessly over uneven ground.
- **Heavy-Duty Gearboxes** are put through the paces during custom-designed lab tests that mimic real-world conditions and obstacles like rocks and stumps, while hundreds of hours in field performance tests prove that these cutters are Bush Hog® Tough.
- **Welded Deck Ring** comes as standard equipment to add rigidity to the deck and reduce the possibility of blade deflection into the deck
- **Cross-Braced Blade Pan** is reinforced to withstand the rigors of harsh brush cutting and impact.
- **5" Wide Blades** chop through dense brush like a heavy axe.
- **Hex-Head Blade Bolts and Bushings** are hardened to provide extra durability and easier blade changes.



Hardened, hex-shaped blade bolts with mating hardened bushings and reinforced blade pans

BH500 SERIES SINGLE-SPINDLE SPECIFICATIONS

MODEL:	BH516
Cutting Width (in)	72
Cutting Height (in)	2 - 12
Cutting Capacity (in)	5
Hitch Type	Cat 2 or 3 Std & QH
Deck Thickness (ga)	7
Sidebands	13" x 1/4"
Driveline	ASAE Cat 5
Driveline Protection	4-Plate Slip-Clutch
Gearbox Rating (PTO)	225
Tractor PTO Speed	540
Minimum Tractor HP	70
Blade Holder	Round
Blades (in)	1/2 x 5 uplift
Blade Tip Speed (FPM)	13,436
Tires	Single 21" Laminated
Safety Shielding	Double Row Chains
Approximate Weight (lbs)	1775
Warranty	6 Year Gearbox Warranty and 1 Year Limited Machine Warranty



IF IT DOESN'T SAY
BUSH HOG®
IT JUST WON'T CUT IT™

2501 Griffin Avenue, Selma, Alabama 36703

Tel: 800-363-6096 | Fax: 334-874-2701

www.bushhog.com

