



**BUSH HOG**®  
Performance You Can Count On™

## 2212 Flex Wing



## Rotary Cutter

### **Bush Hog's Famous Reliability In A Special Duty Cutter**

Designed for smaller tractors, the new Bush Hog® 2212 Flex Wing Rotary Cutters are ideal for rolling, uneven terrain and orchards. They are built with Bush Hog® TOUGH Features so they will deliver superior performance the first day on the job and for years to come.

# Bush Hog®

## 2212 Flex Wing Rotary Cutter

### For 50 to 75 PTO HP Tractors

#### BUSH HOG® TOUGH FEATURES

**TOUGH Heavy Duty Axle Turn Buckles**

**TOUGH Greaseable Axle Pivot Points With Spring Steel Bushings For Extended Wear**

**TOUGH Dual Spring Shock Absorption**



MODEL	2212
Cutting Width	12 ft
Cutting Capacity	1 1/2-inch diameter
Cutting Height	2 to 14 inches
Overall Width and Length (from Clevis to Wheel Hub at Transport Height)	12 ft 8 inches x 13 ft 3 inch
Transport Width (from wing skid to wing skid)	6 ft 8 inches
Tractor PTO	540 RPM
Minimum Tractor HP	50 PTO
Deck Thickness	10 gauge
Side Bands	7 gauge x 12 inches
Gearbox HP	160 -Transfer, 75 - Center, 75 - Wings
PTO Driveline	ASAE Cat. 4 (540 RPM)
Wing Driveline	ASAE Cat. 3
Slip Clutches	(3) Multiple Plate Clutches
Blade Tip Speed	15,604 FPM
Blades	1/2 x 4-inch Uplift with 6-inch Overlap
Type Hitch	Self-Leveling with Swivel Clevis
Wing Flex (Operating)	87° Up to 22° Down
Tires	Choice of Laminated Tire, Used Aircraft Tire,
Axles	Greaseable Pivot Points with Bushings
Wheel Shock Protection	Springs on Center Section
Safety Shielding	Single or Double Row Chains Shielding
Warranty	1 year limited warranty with a 5 year gearbox limited warranty



Turn Buckles



Pivot Points



Dual Spring Shocks

Dealer Info:



**BUSH HOG®**  
Performance You Can Count On™

Bush Hog®, Inc  
2501 Griffin, Ave Selma, AL 36703  
www.bushhog.com (334) 874-2700

Specifications subject to change. ©January 2011 Bush Hog®, Inc