

Bush Hog® TOUGH

2615L Flex Wing Rotary Cutters

Recommended Tractor HP Minimum 60 PTO

BUSH HOG® TOUGH FEATURES

TOUGH 10 Gauge Deck Construction

TOUGH 7 Gauge Strongbacks

TOUGH 1/4 Inch Sidebands

TOUGH Heavy Duty Wheel Hubs And Axle Spindles

TOUGH Independent Spring Cushion At Each Axle Arm

TOUGH Heavy Duty Axle Turn Buckles

TOUGH Greaseable Axle Pivot Points

TOUGH Driveline Safety Retaining Rings

TOUGH 5 Year Gearbox Limited Warranty

TOUGH Powder Coat Paint



MODEL	2615L
Cutting Width	15 ft
Cutting Capacity	2 1/2 inch Diameter
Cutting Height	2 to 14 inches
Overall Width x Length (from Clevis to Wheel Hub at Transport Height)	15 ft 8 inches x 14 ft 10 inches
Transport Width (outside wing skid to outside wing skid)	8 ft 11 inches
Tractor PTO	540 RPM/1000 RPM
Minimum Tractor HP	60 PTO
Deck Thickness	10 gauge
Side Bands	1/4 x 10 1/2 inches
Gearbox HP	235 - Transfer, 190 - Center, 190 - Wings
PTO Driveline	Input: Constant Velocity or Cardan/jackshaft - Cat. 5 (540 RPM) Cat. 4 or 5 (1000 RPM)
Wing Driveline	ASAE Cat. 4
Slip Clutches	(3) 2 - Friction Plates
Blade Tip Speed	16,289 FPM/540 RPM; 16,000 FPM/1000 RPM
Blades	1/2 x 4 inch Uplift with 6 inch Overlap
Type Hitch	Self Leveling with Perma-Level Hitch® or 2 Inch Ball Hitch or Swivel Clevis Hitch
Wing Flex (operating)	87° Up to 22° Down
Tires	Laminated Tire, Used Aircraft Tire, Foam Filled Used Aircraft Tire, Pneumatic 15 inch wheel (tire not included)
Axles	Single or Dual Wing Axles, Dual or Walking Tandem on Center
Wheel Shock Protection	Independent Springs on Each Axle
Deflectors	Standard Front Belting and Rear Band, Optional Front and Rear Chains
Options	Chain Shielding, Valve & Stand Kit, Deck Rings
Warranty	1 year limited warranty with a 5 year gearbox limited warranty

FEATURES

- Perma Level Hitch • Cylinder style anti wrap device around lower gearbox housing
- High blade tip speeds • Deep sidebands • Heavy duty wheel hubs • Quick detach gearbox shields

BUSH HOG EXCLUSIVE:

Driveline safety retaining rings