

SERIES: 1800 | 2100 | 2200 | 2800 | 4100 | 5100



FLEX-WING

ROTARY CUTTERS

FLEX-WING ROTARY CUTTERS



4115 FLEX-WING ROTARY CUTTER



HP REQUIRED
60 HP



CUTTING CAPACITY
4" DIAM.



HITCH TYPE
**PERMA-LEVEL+
OR BALL HITCH**

10
YEAR
GEARBOX LIMITED
WARRANTY



GET SPECIFICATIONS
AND ADDITIONAL
PRODUCT FEATURES

Heavy-Duty Flex-Wing

Building upon the success of our legendary Heavy-Duty Flex-Wing lineup, the New 4115 Flex-Wing is built for the harshest cutting conditions. Designed to cut heavy grasses and brush up to 4" in diameter, these New 15' Flex-Wings are serious machines for serious users. Perfectly at home maintaining rights-of-way and roadsides or long days clipping the back 400, these cutters get the job done in any environment, day in and day out. New performance and convenience features like seriously upgraded axles, EZ blade changes with hardened hex-head bolts and bushings, and EZ-adjust leveling rods make your life easier and worry-free. Our new and improved axles glide over obstacles, while significantly reducing shock loads for an improvement you can see and feel in the tractor seat. Heavily-braced, 7ga smooth-top decks shed debris and water for easier cleanup. Gearbox stand plates are thicker and gusseted for improved strength and durability. Our Perma-Level+ Hitch has received additional reinforcements and quality of life features like rollover and clevis stops for easier tractor hookups. Standard equipment includes convenience features like EZ-lube drivelines, increased tongue transport height, and hydraulic hose handles to reduce slipping and improve ergonomics. Then when not in use, the hoses can be safely stored in the holder on the tongue.

FEATURES



Bespoke rubber isolator bank on the center axle absorbs damaging shock loads before going through the deck and eventually to the tractor



Custom-tuned suspension system reduces axle shock loads by 51%



Hardened hex-head blade bolts and bushings make for quick and easy blade changes



Sideband integrity is protected by durable and replaceable 1/2" thick cast skids along with a 41% longer front to back formed skids



Find more product features and options at **BUSHHOG®.com**

5110 FLEX-WING ROTARY CUTTER



HP REQUIRED
70 HP



CUTTING CAPACITY
5" DIAM.



HITCH TYPE
**PERMA-LEVEL+
OR BALL HITCH**



10
YEAR
GEARBOX LIMITED
WARRANTY



GET SPECIFICATIONS
AND ADDITIONAL
PRODUCT FEATURES

New Extreme-Duty Right-Of-Way Single Flex-Wing

Designed to cut heavy grasses and brush up to 5" in diameter, these New 10' Flex-Wings are serious machines for serious users. These cutters are perfectly at home maintaining right-of-ways, levees, and roadsides in any environment, day in and day out. New performance and convenience features like seriously upgraded axles, EZ-change blade bolts, 3/4" blade carriers with 5" blades, and EZ-adjust leveling rods make your life easier and worry-free. Our new and improved axles glide over obstacles, while reducing shock loads for an improvement you can see and feel in the tractor seat. Heavily-braced, 1/4" smooth-top decks shed debris and water for easier cleanup. Gearbox stand plates are thicker, reinforced and gusseted for improved strength and durability. Our Perma-Level+ Hitch has received additional reinforcements and quality of life features like rollover and clevis stops for easier tractor hookups. Standard equipment includes convenience features like EZ-lube drivelines, increased tongue transport height, and hydraulic hose handles to reduce hand slipping and improve ergonomics; then when not in use, the hoses can be safely stored in the holder on the tongue.

FEATURES



Reinforced axle tubes with custom rubber isolator bank on the center axle absorbs damaging shock loads before going through the deck and eventually to the tractor



3/4" uplift blade carrier is equipped with 5" blades and hardened hex-head blade bolts and bushings that make blade changes quick and easy



Custom-tuned rubber isolator pads absorb shock at each axle



1/4" x 13" sidebands are protected by 1/2" replaceable cast skids and extended front to back built-in skids



5115 FLEX-WING ROTARY CUTTER



HP REQUIRED
70 HP



CUTTING CAPACITY
5" DIAM.



HITCH TYPE
**PERMA-LEVEL+
OR BALL HITCH**

10
YEAR
GEARBOX LIMITED
WARRANTY



GET SPECIFICATIONS
AND ADDITIONAL
PRODUCT FEATURES

New Extreme-Duty 15' Flex-Wing

Designed to cut heavy grasses and brush up to 5" in diameter, these New 15' Flex-Wings are serious machines for serious users. Perfectly at home maintaining rights-of-way and roadsides or long days clipping the back "400", these cutters get the job done in any environment, day in and day out. New performance and convenience features like seriously upgraded axles, EZ-change blade bolts, 3/4" Uplift Blade Carriers, and EZ-adjust leveling rods make your life easier and worry-free. Our new and improved axles glide over obstacles, while significantly reducing shock loads for an improvement you can see and feel in the tractor seat. Heavily-braced, 1/4" smooth-top decks shed debris and water for easier cleanup. Extreme-Duty gearbox stands are thicker, braced and gusseted to withstand the harshest cutting environments. Our Perma-Level+ Hitch has received additional reinforcements and quality of life features like rollover and clevis stops for easier tractor hookups. Standard equipment includes convenience features like EZ-lube drivelines, increased tongue transport height, and hydraulic hose handles to reduce hand-slipping and improve ergonomics. Then when not in use, the hoses can be safely stored in the holder on the tongue.

FEATURES



Reinforced axle tube with custom rubber isolator bank on the center axle absorbs damaging shock loads before going through the deck and eventually to the tractor



The New 5115 has substantial structural framework with Hex-Shaped Deck Rings to add stiffness to and protect the deck structure while distributing clippings more evenly



New Cast Walking Tandem Axle selection strolls over rough terrain with ease



Leveling the deck is made easy with our new cam adjuster



Find more product features and options at **BUSHHOG®.com**



BUSH HOG® FLEX-WINGS

SPECIFICATION COMPARISON

	1812	1815	2120	2215	2814	2820	4110	4115	5110	5115
CUTTING WIDTH	12'	15'	20'	15'	13' 6"	20'	10'	15'	10' 6"	15'
CUTTING HEIGHT	1 ½" - 14"	1 ½" - 14"	1 ½" - 14"	1 ½" - 14"	1 ½" - 14"	1 ½" - 14"	1 ½" - 14"	1 ½" - 14"	1 ½" - 16"	1 ½" - 16"
CUTTING CAPACITY	1 ½"	2 ½"	2"	3 ½"	3"	3"	4"	4"	5"	5"
APPROXIMATE WEIGHT (LB)	3,350	4,300	6,200	4,800	6,100	7,100	6,400	6,500	6,600	6,900
TONGUE WEIGHT (LB)	1,100	1,700	2,100	1,800	2,600	2,600	1,900	2,000	2,200	2,300
DECK THICKNESS, CENTER (GA)	10	10	10	10	11/10	11/10	7	7	1/4"	1/4"
DECK THICKNESS, WINGS (GA)	10	10	10	10	10	10	7	7	1/4"	1/4"
SIDE BANDS	1/4" x 11 ½"	1/4" x 12"	1/4" x 12"	1/4" x 13 ½"	1/4" x 13 ½"	1/4" x 13 ½"	1/4" x 13 ½"	1/4" x 13 ½"	1/4" x 13 ½"	1/4" x 13 ½"
TRANSFER GEARBOX (HP)	160	160	160	250	250	250	250	250	250	250
CUTTING GEARBOX (HP)	65	130	130	210	225	225	225	225	225	225
GEARBOX WARRANTY (YRS)	10	10	10	10	10	10	10	10	10	10
INPUT DRIVELINES	Cat. 4	Cat. 5	Cat. 6	Cat. 6	Cat. 6	Cat. 6	Cat. 6	Cat. 6	Cat. 6	Cat. 6
CUTTING DRIVELINES	Cat. 3	Cat. 4	Cat. 5	Cat. 4	Cat. 5	Cat. 5	Cat. 4	Cat. 4	Cat. 5	Cat. 5
MINIMUM TRACTOR PTO HP	50	60	70	60	90	90	60	60	70	70
TRACTOR PTO SPEED	540	540 or 1,000	540 or 1,000	540 or 1,000	540 or 1,000	540 or 1,000	540 or 1,000	540 or 1,000	540 or 1,000	540 or 1,000
BLADES	1/2" x 3"	1/2" x 4"	1/2" x 4"	1/2" x 4"	1/2" x 4"	1/2" x 4"	1/2" x 4"	1/2" x 4"	1/2" x 5"	1/2" x 5"
BLADE HOLDER	11ga Oval	7ga Round	7ga Round	7ga Round	7ga Round	7ga Round	7ga Round	7ga Round	3/4" Uplift	3/4" Uplift
BLADE TIP SPEED (FPM)	14,504	15,000	16,000	16,286	15,936	15,936	16,268	16,268	16,268	16,268
DEFLECTOR TYPE	Single or Double Chains	Single or Double Chains	Single or Double Chains	Single or Double Chains	Double Chains	Single or Double Chains	Double Chains	Single or Double Chains	Double Chains	Double Chains
TIRES	Laminated Pneumatic Foam-Filled	Laminated Pneumatic Foam-Filled	Laminated Pneumatic Foam-Filled	Laminated Pneumatic Foam-Filled	Laminated Pneumatic Foam-Filled	Laminated Pneumatic Foam-Filled	Laminated Pneumatic Foam-Filled	Laminated Pneumatic Foam-Filled	Laminated Pneumatic Foam-Filled	Laminated Pneumatic Foam-Filled

Specifications and design subject to change without notice.



Find more product specifications, features and options at **BUSHHOG®.com**